

# INSTATUT WŁOKIENNICTWA Textile Research Institute

92-103 Łódź, ul. Brzezińska 5/15, tel. +48(0)42 6163101, fax.+48(0)42 6792638



## LABORATORY OF FLAMMABILITY TESTING

90-520 Łódź, ul. Gdańska 118, tel.: +48(0) 42 2534435, +48(0)42 2534436, fax.+48(0)42 2534490

### TEST CERTYFICATE ON FLAMMABILITY TESTING OF MATTRESSES

No 140 / BP / 15

#### Test method:

PN-EN 597-1:1999 Furniture. Assessment of the ignitability of mattresses and upholstered bad bases. Part 1: Ignition source: Smouldering cigarette..



#### Orderer:

"TOPTEXTIL" Sp. z o.o. ul. Wadowicka 12 30-415 Kraków



# **Subject of testing:**

Upholstery composition:

- mattress woven fabric named GALERIA BED,
   composition: 70% Polyester, 30% Polypropylene; weight: 125 g/m²
- CM-3040 foam, flame-retardant

Testing sample of the woven fabric and its characteristic supplied by the Orderer.

## Results of testing:

Standard	Test method	Result		
PN-EN 597-1:1999	Ignition source: smouldering cigarette	Neither progressive smouldering ignition nor flaming ignition occurred.		

The above test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the mattress, mattress pillow or upholstered bed base in use.

Tests performed by:

Andrzej Kubacki, technician

Report authorized by:

Laboratorium Badań Palności Wyrobów KIEROWNIK

mgr inż. Małgorzata Szejna

Sample received on: Test performed on: 21.04.2015 19.05.2015

#### NOTES:

- 1. The Testing results refer only to the tested sample.
- 2. Test Certificate consists of 2 pages.
- 3. Test Certificate must not be reproduced in another way, than as a whole without a prior written consent of the Testing Laboratory.
- 4. The Orderer using this Test Certificate is responsible for the conformity between the product and sample submitted for testing.



Test Certificate No 140 / BP / 15 continued

## **DETAILED TESTING RESULTS**

Climate conditions: temperature  $(23 \pm 2)$  °C;

humidity  $(50 \pm 5) \%$ 

Testing conditions: temperature 21 °C;

humidity 40 %

Specimen size:

length 450 mm x width 350 mm x depth 75 mm

Criteria		Cigarette		Place of the smouldering	
		1	2	cigarette	
Smouldering criteria	Unsafe escalating combustion	NO	NO	Cigarettes 1 and 2 placed on the upper flat side of the mattress.  Maximum cigarette	
	Test assembly consumed	NO	NO		
	Smoulders through thickness	NO	NO		
	Smoulders more than 1 hour	NO	NO		
	Smoulders in distance bigger than 50 mm from place of the ignition source	NO	NO		
Flaming criteria	Occurrence of flames	NO	NO	smouldering time: 15 minutes 30 seconds	

**Result of testing:** Neither progressive smouldering ignition nor flaming ignition occurred.



END OF THE TEST CERTIFICATE